









| MCV 400 L SPECS | | | |
|-------------------------------|--|-------------------------------------|---|
| Category | Coach | Dimensions | |
| Chassis | OH 1626L | Overall Length (mm) | 11,895 |
| GVW (Kg) | 16,000 | Overall Width (mm) | 2,550 |
| Chassis components | | Overall Height (mm) with A/C | 3,425 |
| Engine: | | Wheelbase (mm) | 5,955 |
| Cylinders/ Displacement (cm³) | 6 Cylinders vertical in line /6374 cubic centimeter | Front Overhang (mm) | 2,490 |
| Туре | MB OM 906 LA.III | Rear Overhang (mm) | 3,450 |
| Output (kW) | 191 KW (260hp) @2200 rpm | Standing Height Center Aisle (mm) | 1,910 |
| Torque | 950 Nm @1600-1200 rpm | Approach/ Departure Angles (degree) | 9/8 |
| Smoke Emission Standard | Euro III (optional Euro V) | First Step Height (mm) | 320 |
| Transmission | Mercedes-Benz G6 ,85 manual speeds | Ground Clearance (mm) Chassis | 257 |
| Retarder | Voith 123 retarder (optional) | Luggage Capacity (m³) | Up to 7 (without toilet) |
| Clutch | MF 395, single disc, dry, servo hydraulic actuated | Capacity: | |
| Steering | Power steering ZF - 8097 | Seating Passengers | 45 (with toilet) |
| Brake System | Dual-circuit, full air system | | 47 (with/ without toilet) |
| Parking Brake | Spring loaded rear brake chambers with air release | | 49 (with tollet) |
| Additional Brake | Exhaust brake/top brake (optional) | Standard Body Features | |
| Front Axle | MB VL 8/3 D5500- 6.5- Kg, forged steel "I" beam | Number of Doors | 2 (front & center) |
| Rear Axle | MB HH 08/4 DL - 10500 Kg (ratio 5.22) , center housing with pressed-in axle steel tubes | Type of Doors | Plug type |
| | | Door Actuation | Electro-pneumatic |
| Suspension: | | Windscreen | One piece (glued) |
| Front Axle | Air suspension with 2 air bellows, internal auxiliary knocker and 1 leveling valve, two telescopic double acting shock absorbers, stabilizer | Side Windows | Single glazing (tinted gray %50) |
| | | Roof Hatches | Two emergency type |
| Rear Axie | Air Suspension with 4 air bellows, external auxiliary knocker and 2 leveling valve, two telescopic double acting shock absorbers, stabilizer | Type of Seats | Luxury reclining seats with 2 point seatbelt |
| | | Driver Seat | Air suspension |
| | | Driver Window | Powered |
| Wheel Rims | Steel 8.25 x 22.5 | A/C System | Cooling capacity 37kW |
| Tyres | 11 R22.5PR16 | Mirrors | Two exterior electric & heated mirrors |
| Alternator (V/A) | 2 x 80/28 A | Insulation | Effective insulation against heat & sound |
| Batteries (V/Ah) | 2 x 170/12 Ah | A/V System | A/V system with two 19' monitors |
| Fuel Tank Capacity (liters) | 380 | Other Standard Features: | Dashboard top loading fridge 60L |
| Chassis Optional Features | | Type of Seats | Front & rear fog light |
| | ABS anti-blocking system ASR anti-skid adjustment system | Type of Seats | Manual sun visor for windscreen & driver side window |





